

# Cabinet Water Softener



## eSoft Eco

Model	5 Litre Cabinet	8 Litre Cabinet	10 Litre Cabinet	20 Litre Cabinet	30 Litre Cabinet
<b>Part Number</b>	1100342	1101784	1035556	1036428	1036687
<b>Softener Specification</b>	8 x 13"	10 x 13"	8 x 17"	8 x 24"	10 x 35"
<b>Total Height</b>	490mm	510mm	580mm	750mm	1050mm
<b>Total Depth (Including Fittings)</b>	520mm	500mm	520mm	520mm	580mm
<b>Width</b>	270mm	340mm	270mm	270mm	350mm
<b>Maximum Working Pressure</b>	5bar	5bar	5 bar	5 bar	5 bar
<b>Minimum Working Pressure</b>	1.7bar	1.7 bar	1.7 bar	1.7 bar	1.7 bar
<b>Service Flow Rate</b>	10 L/min	10 L/min	10 L/min	15 L/min	23 L/min
<b>Pressure Drop at Service Flow</b>	0.2	0.2	0.2 bar	0.35 bar	0.55 bar
<b>Resin Volume</b>	5	8	8 litres	20 litres	30 litres
<b>Minimum Supply Flow Rate</b>	8	8	8 L/min	8 L/min	8 L/min
<b>Salt Use per Regeneration</b>	0.75kgs	1.2kgs	1.2 kgs	3.0 kgs	4.5 kgs
<b>Inlet / Outlet Connections</b>	¾" BSPM	¾" BSPM	¾" BSPM	¾" BSPM	¾" BSPM
<b>Overflow Connections</b>	½"	½"	½"	½"	½"
<b>Softening Capacity @ 300ppm</b>	830 litres	1330 litres	1330 litres	2500 litres	5000 litres



**eSoft Eco**  
Installation Video

## eSoft Pro

Model	5 Litre Cabinet	8 Litre Cabinet	10 Litre Cabinet	20 Litre Cabinet	30 Litre Cabinet
<b>Part Number</b>	1033167	1101783	1020967	1020968	1015567
<b>Softener Specification</b>	8 x 13"	10 x 13"	8 x 17"	8 x 24"	10 x 35"
<b>Total Height</b>	523mm	550mm	625mm	800mm	1095mm
<b>Total Depth (Including Fittings)</b>	490mm	460mm	440mm	440mm	580mm
<b>Width</b>	270mm	340mm	270mm	270mm	350mm
<b>Maximum Working Pressure</b>	5 bar	5 bar	5 bar	5 bar	5 bar
<b>Minimum Working Pressure</b>	1.7 bar	1.7 bar	1.7 bar	1.7 bar	1.7 bar
<b>Service Flow Rate</b>	10 L/min	10 L/min	10 L/min	15 L/min	23 L/min
<b>Pressure Drop at Service Flow</b>	0.2 bar	0.2 bar	0.2 bar	0.35 bar	0.55 bar
<b>Resin Volume</b>	5 litres	8 litres	8 litres	20 litres	30 litres
<b>Minimum Supply Flow Rate</b>	5 L/min	8 litres	8 L/min	8 L/min	8 L/min
<b>Salt Use per Regeneration</b>	0.75 kgs	1.2 kgs	1.2 kgs	3.0 kgs	4.5 kgs
<b>Inlet / Outlet Connections</b>	¾" BSPM	¾" BSPM	¾" BSPM	¾" BSPM	¾" BSPM
<b>Overflow Connections</b>	½"	½"	½"	½"	½"
<b>Softening Capacity @ 300ppm</b>	830litres	1330 litres	1330 litres	2500 litres	5000 litres



**eSoft Pro**  
Installation Video

\*All information correct at time of going to print. May be subject to change.

**E** info@epswater.ie

**W** epswater.ie

**Rethinking Water**

Mallow, Co. Cork  
T 022 31200

Ballyhaunis, Co. Mayo  
T 094 9633500

Mountrath, Co. Laois  
T 057 8732279

Naas, Co. Kildare  
T 045 843614